

Sistema di illuminazione lineare. Estruso in alluminio verniciato a polvere nella variante nero o bianco, o sottoposto a processo di anodizzazione per la versione in alluminio. Diffusore in pmma opaco bianco o nero. Può essere installato a plafone, sospensione o applique. Nelle versioni sospensione e applique possibilità di scelta tra mono e biemissione. Prodotto completo di scheda led e driver on board.

Prodotto disponibile anche in versione Matericallight con rivestimenti formati da elementi naturali come la pietra Arenaria, Cemento e da processi di ossidazione del Ferro.

Linear lighting system. Extruded aluminum powder coated in the black or white version, or subjected to an anodizing process for the aluminum version. Diffuser in matt white or black pmma. It can be installed on the ceiling, suspended or wall mounted. In the suspension or wall-mounted versions it is possible to choose between mono and biemission. Product complete with LED board and driver on board.

Product also available in a Matericallight version with coatings made up of natural elements such as sandstone, cement and iron oxidation processes.


Specifiche Tecniche

Technical specifications



Made in Italy

| | |
|--|--|
| Nome prodotto Product name | Liberty |
| Codice prodotto Product code | L06 |
| Applicazione Application | Plafone Ceiling Sospensione Suspension Applique Applique |
| Colore CTT CTT Color | 2700K 3000K 4000K |
| Lumen Lumen | monoemission 840lm biemission 1680lm |
| Resa cromaica Color rendering | CRI>80 |
| Fascio luminoso Beam angle | 160° |
| Potenza Power | monoemission 7W biemission 2x5W |
| Tensione nominale di funzionamento Rated operating voltage | AC 220-240V 50/60Hz |
| Caratteristiche Alimentatore Power supply features | ICS Driver pf>0.99 |
| Classe di isolamento Insulation Class | Classe I |
| Dimmerazione (su richiesta) Dimming (on request) | Triac |
| Grado di protezione IP IP Class | IP40 |
| Materiali Materials | Alluminio Aluminium PMMA PMMA |
| Finiture Finishes | Bianco White or Nero Black or Anodizzato Anodized |
| Accessori Accessories | Kit Sosp. Kit Applique Kit Plafone Black Diffuser Prismatic Diffuser Ceiling Rose |
| Versione Matericallight Matericallight version | Cemento Dark (CD) Cement Clear(CC) Aquarius(CA) Corten(CO) Arenaria Arabik(AR) Arenaria Libic(LB) Oxide(OX) Travertino Natural(TN) |



Certificazioni e Standard

Certifications and Standards

- Classe efficienza energetica|Energy efficiency class : Classe A
- Consumo energetico|Energy consumption (kWh/1000ore) : 7 mono | 10 biem
- Certificazioni|Certifications : CE, Rohs.